



1/2" Superflexible Foam Dielectric, FSJ Series – 50-ohm



FSJ4-50B

Description	Type No.
Cable Ordering Information	
Standard Superflexible Cable	
1/2" Standard Cable, Standard Jacket	FSJ4-50B
Fire Retardant Cables	
1/2" Fire Retardant Jacket (CATVX)	FSJ4RN-50B
1/2" Fire Retardant Jacket (CATVR)	FSJ4RN-50B
Low VSWR and Specialized Cables	
1/2" Low VSWR, specify operating band	FSJ4P-50-(**)
Phase Stabilized and Phase Measured Cable	See page 590
Jumper Cable Assemblies – See page 584	
** Insert suffix number from "Low VSWR Specifications" table, page 487	
Characteristics	
Electrical	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	10.2
Velocity, percent	81
Peak Power Rating, kW	15.6
dc Resistance, ohms/1000 ft (1000 m)	
Inner	0.82 (2.69)
Outer	1.00 (3.28)
dc Breakdown, volts	2500
Jacket Spark, volts RMS	5000
Capacitance, pF/ft (m)	25.2 (82.7)
Inductance, µH/ft (m)	0.0625 (0.205)
Mechanical	
Outer Conductor	Copper
Inner Conductor	Copper-Clad Aluminum
Diameter over Jacket, standard jacket, in (mm)	0.52 (13.2)
Diameter over Jacket, fire-retardant jacket, in (mm)	0.53 (13.5)
Diameter over Copper Outer Conductor, in (mm)	0.48 (12.2)
Diameter Inner Conductor, in (mm)	0.142 (3.6)
Minimum Bending Radius, in (mm)	1.25 (32)
Number of Bends, minimum (typical)	20 (50)
Bending Moment, lb-ft (N·m)	2.0 (2.7)
Cable Weight, lb/ft. (kg/m)	0.14 (0.21)
Tensile Strength, lb (kg)	175 (80)
Flat Plate Crush Strength, lb/in (kg/mm)	110 (1.9)

Attenuation and Average Power Ratings

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.070	0.231	15.6
1	0.100	0.327	15.6
1.5	0.122	0.401	15.6
2	0.141	0.463	15.6
10	0.318	1.04	10.1
20	0.453	1.49	7.07
30	0.557	1.83	5.75
50	0.724	2.38	4.42
88	0.971	3.19	3.30
100	1.04	3.41	3.08
108	1.08	3.55	2.96
150	1.28	4.21	2.49
174	1.39	4.56	2.30
200	1.50	4.91	2.14
300	1.86	6.09	1.72
400	2.17	7.12	1.48
450	2.31	7.59	1.38
500	2.45	8.04	1.31
512	2.48	8.15	1.29
600	2.71	8.89	1.18
700	2.95	9.68	1.09
800	3.18	10.4	1.01
824	3.23	10.6	0.991
894	3.38	11.1	0.947
960	3.52	11.6	0.909
1000	3.60	11.8	0.889
1250	4.09	13.4	0.783
1500	4.54	14.9	0.705
1700	4.88	16.0	0.656
1800	5.05	16.6	0.634
2000	5.37	17.6	0.597
2100	5.53	18.1	0.580
2200	5.68	18.6	0.564
2300	5.83	19.1	0.549
3000	6.84	22.4	0.469
3400	7.38	24.2	0.435
4000	8.15	26.7	0.394
5000	9.35	30.7	0.343
6000	10.5	34.4	0.306
8000	12.6	41.4	0.254
10000	14.6	47.9	0.220
10200	14.8	48.5	0.217

Standard Conditions:

For attenuation. VSWR 1.0, ambient temperature 20°C (68°F).

For Average Power, VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F), no solar loading.